ATF 8 Gear

DESCRIPTION

High quality synthetic automatic transmission fluid with low viscosity for a more responsive transmission. Suitable for automatic transmissions.

APPLICATION

BARDAHL ATF 8 Gear has excellent stability and fluidity at low temperatures. Ideal for cold starts. The **ATF 8 GEAR** can be used in many automatic transmissions and has been formulated for the lubrication of ZF 8HP (8HP45, 8HP55, 8HP70, 8HP90 ...) transmissions as it has a strong fuel economy contribution. It can also be used for some 6HP (VAG, BMW models).

SPECIFICATIONS

This product meets the following performance levels:

AISIN WARNER	JWS AW-1
BMW/MINI	83 22 0 142 516, 83 22 0 163 514, 83 22 0 397 114
CHRYSLER	P/N 05127382AA P/N 68043742AA P/N 68157995AA
FORD MERCON	LV
GM DEXRON	VI GMN10060
HONDA	DW-1
HYUNDAI/KIA	40000C90SG /NWS-9638 T-5 /SP-IV/ SPH-IV
JASO	M315 TYPE 1A
JAGUAR LAND ROVER	Fluid 8432/ LR0022460/ TYK500050
MB	236.12/ 236.14/ 236.15/ 236.17/ 236.41
MASERATI	P/N 231603/ P/N 231603
MAZDA	ATF FZ
MITSUBISHI	ATF-J3
NISSAN	MATIC S
PORSCHE	P/N 000 043 304 00
SAAB	AW-1/P/N 93 165 147
TOYOTA	ATF WS including TOYOTA HYBRID SYSTEM
VAG	VW G 052 533/G 055 005 (ZF lifeguardfluid 6)/G 055 162 (ZF lifeguardfluid 6+)/G 055 540/G 060 162 (ZF lifeguardfluid 8)
ZF	6HP/8HP/9HP/ZF-TE-ML 09

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

PROPERTIES

✓ **High viscosity index** ensuring good stability,
✓ Longer lifespan,
✓ **Very low pour point,**
✓ Very good thermal stability and anti-oxidation protection,
✓ Anti-wear, anti-corrosion and anti-foam,
✓ High-performance anti-friction additives,
✓ Inert for seals and non-ferrous metals,
✓ Good resistance to vibrations,
✓ Quick commissioning during cold starts,
✓ Viscosity to avoid overconsumption (fuel economy),
✓ **Red color**.

TECHNICAL DATA

Density at 15°C	Kg/l	0,843
Viscosity 40°C	mm2/s	29,53
Viscosity 100°C	mm2/s	5,83
Viscosity Index		155
Flash point COC, °C	°C	>200
Pour point, °C	°C	-42

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling: All safety information on the handling and use of this product is provided in the Material Safety Data Sheet. Always check the manufacturer car manual before use.

Storage: it is recommended to use the product within 60 months. It must be stored in the original sealed packaging, protected from light, moisture and excessive temperatures.

REFERENCES & PACKING

36871	12 x 1L
36873	3 x 5L
36878	20L
36874	60L
36877	205L

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com